



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

Reduction of Allowed Inventory When Chemicals are Located in Close Proximity with Explosives

Y. P. Chong, S. N. Nguyen

September 29, 2006

Recognizing Accomplishments & Contributions to Health &
Safety

Livermore, CA, United States

October 2, 2006 through October 3, 2006

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

Reduction of Allowed Inventory When Chemicals are Located in Close Proximity with Explosives

By Y.P. Chong and S.N. Nguyen

presented at the Hazards Control Department
REACHS Conference
on October 2-3, 2006

This work was performed under the auspices of the U.S. Department of Energy by
University of California, Lawrence Livermore National Laboratory under Contract W-7405-
Eng-48.

Objective

- To determine the allowed inventory of *chemicals* stored in the same bay, building or magazine, i.e., in close proximity, with *high explosives (HE)* that would, in the event of an accident. result in acceptable risks to colocated workers and the public.

First Moderate Hazard Nonnuclear Facility SBD

- This work was performed to support the development of the Safety Basis Document (SBD) for the Chemistry & Materials Science (CMS) Site 300 Facility.
- This is the first Moderate Hazard SBD prepared according to the *ES&H Manual*, Document 3.1, *Nonnuclear Safety Basis Program* and submitted to DOE for approval.

Background Information

- CMS Site 300 Facility consists of >50 buildings and service magazines scattered throughout S300.
- The Facility is divided into three groups: Process Area, Chemistry Area and the Explosives Waste Treatment Facility (EWTF).
- Their safety bases are the
 - Bases for Interim Operation (BIOS) May 2000 - Process and Chemistry Areas
 - Safety Analysis Report (SAR) 2003 - EWTF.
- This SBD replaces the two BIOS and the EWTF SAR.

Chronology

- CMS initiates effort to replace the two BIOS in 2002. Walt Wajda started the project but a budgetary problem postponed it until May 2004.
- The next completion date was May 2005 (before the BIOs expired).
- The submitted SBD is under review by DOE.

Site Issues

- Determine the effects of the airborne releases to the S300 colocated worker at 100 m distance, and to the offsite public.
- Some CMS buildings are located only a few hundred meters from the S300 offsite boundary.

Technical Issues

- Chemicals are used or stored in the same bay, same cell with high explosives (HE).
- In the past, explosives hazards are analyzed separately from chemical hazards in accident scenarios. Now, the scenarios must include explosions that may disperse the chemicals.
- No available data exists on the airborne release fractions for most chemicals of interest.

Safety Basis Evaluation

- *ES&H Manual Document 3.1, Nonnuclear Safety Basis Program, LLNL*
- Chemicals - Temporary Emergency Exposure Limit (TEEL) values & Q values for the colocated worker at 100 m and the public at nearest offsite boundary to facility
- Explosives – Quantity-Distance calculations

Chemical Samples & Explosives Range

- Sample chemicals presented here out of a large number studied
 - Uranium (U), Beryllium (Be)
- HE mass range studied for operational flexibility
 - 5, 10, 25, 50, 100 kg

Chemical Inventories Allowed at 100 m for 5 kg HE

- Evaluated independently (LSI Q value)

–U 2300 kg

–Be 380 kg

- Evaluated in close proximity (code)

–U 170 kg (Q/13.5)

–Be 16 kg (Q/24)

Sample Results for Uranium in Close Proximity with 5 kg HE

- For colocated worker at 100 m, the allowed inventory is reduced by a factor of 13.5.
- For offsite public at 400 m, the reduction is a factor of 5.5x lower than the Q value.
- For offsite public at 900 m, the reduction factor is 11x lower than the Q value.

Sample Results for Uranium in Close Proximity with 100 kg HE

- At 100 m (colocated worker), the allowed inventory is higher by 6.5x.
- At 400 m (offsite public), the allowed inventory is 1.4x higher than the relevant Q value.
- At 900 m (offsite public), the reduction is 1.7x lower than the relevant Q value.

Sample Results for Beryllium in Close Proximity with 5 kg HE

- At 100 m (colocated worker), the allowed inventory is reduced by 20x.
- For offsite public at 400 m, the reduction is 180x lower than the Q value.
- For offsite public at 900 m, the reduction is 400x lower than the Q value.

Summary

- The allowed inventories of chemicals that are placed in close proximity with high explosives can be much lower than their Q values provided in the *ES&H Manual*, Document 3.1.
- Studying a range of HE masses permits operational flexibility in the chemical and explosives inventories allowed in a bay or cell.

Conclusion

- In order to properly protect the colocated worker and the offsite public, the allowed inventories of chemicals located in the same bay, cell, or magazine with high explosives have to be evaluated carefully. In an accident event, their exposure to the chemicals will then be limited to the approved safe level.
- These studies provide an excellent tool for facility management to determine accurately the allowed inventories that would not pose unacceptable risks to colocated worker and the offsite public.